

POLYGRAB

POLYSTYRENE SPRAY ADHESIVE



Features

- Ease Of Application
- Fast Bond Time
- Long Open Time
- High Bond Strength
- Completely Portable
- Maintenance Free

Technical Data

Chemical Name	Sprayable contact adhesive
Appearance	Blue Liquid
Coverage	17 sqm Per Kg
Glue Solids	28-30%
Shelf Life	1 Year

“A Revolution In The Industry”

Application

All surfaces to be bonded should be dry, clean, dust and grease free. To apply Polygrab hold the gun parallel to the work surface and administer a generous coat of adhesive, coverage of at least 80 to 100% is recommended.

Before bringing the two substrates together ensure that the adhesive is allowed to tack up, i.e. to be able to touch without any transference to the fingers. You can now bring the surfaces together using uniform pressure and the workpiece can be instantly handled.

It is important to test all the substrates to be bonded before going into production or undertaking a large contract. It is the responsibility of the user to ensure the adhesive's suitability to the substrates. If you are unsure, please do not hesitate to contact Gemini Adhesives technical department who will be more than happy to assist.



This container will be collected for recycling
FREEPHONE
0800 3284267
INTERNATIONAL STANDARD
ISO 14021
TYPE II ENVIRONMENTAL CLAIM

gemini
...creating lifetime bonds

ADHESIVES | R & D | EXTRUSIONS | SUSTAINABILITY

Gemini Adhesives Limited, Unit 1 Leach Way, Blidworth, Mansfield, NG21 0RU (UK)
Freephone Sales Line UK: 0800 3284267 **Email: info@geminiadhesives.com**

www.geminiadhesives.com